

Packaging Aids Combination Shrink System DEM 450

DEM 450 Shrink Wrapping Machines

The DEM 450 combination L-bar Sealer and Shrink tunnel unit allows packing, sealing and shrinking product in centerfold shrink-wrap film. The DEM 450 series can be used for a wide range of products thanks to its precise temperature and speed controls. Operation is simple and efficient. Our DEM Series shrink systems are heavy duty and require a minimum of maintenance. They can be operated up to seven days a week, 24 hours per day. The DEM series is available in either a manually operated (DEM 450T) or a semi-automatic (DEM 450 SA)

Standard Features and Benefits of DEM 450

- L-bar sealer capable of sealing product up to 20"L x 13"W x 7"H
- Variable temperature, variable blower speed and variable conveyor speed
- Compensated L-bar sealing capability with pneumatically operated L-bar (DEM 450 SA model).
- Pneumatic L-bar arm with built in safety capable of automatic re-cycling with adjustable delay between cycles
- Convenient scrap drop and collection area for trimmed film
- Easily relocate-able, safe electronic film perforation system
- Contemporary microprocessor controls with easy-to-use operator display system for fast, easy operator programming of controllable functions. Job settings are easy to save and retrieve reducing setup between jobs
- Take away, and tunnel conveyors have common height adjustment, but separate speed controls for setting optimum performance



Specifications:

	DEM 450
Machine Dimensions:	82" L x 35" W x 62" H
Maximum product size:	20" L x 13" W x 7" H
Power:	220 Volt, 3-phase, 6000 watt
Air:	Unit meets CE electrical standards 87 PSI

Options:

- Pneumatic sealer arm on DEM 450 SA
- Blower Table