

SEAL AND SHRINK IN JUST ONE STEP

AUDION
DEMPACK
SHRINK PACKAGING

H 22



H 18



The *Dempack* Family of Compact, chamber style mini shrink systems provides both a simple operator interface and simple, one step seal and shrink operation.



Other products Shrink Wrapped with *DEMPACK Mini Shrink* Units include:

Books, Toys, Plastic Models, Tools, Hardware, Computer Hardware and Software, Stationary, Printing Supplies, Posters, Calendars, Art Kits, Picture Frames, Vinyl Records, Audio Cassettes, Video Cassettes, CD's, DVD's, Business Forms, Sporting Goods, Electric Tools, Automotive Parts, Textiles, Frozen Pizza, Bakery Boxes, Fruit Baskets, Bar Soap, Rope and many more...

AUDION AUTOMATION *DEMPACK*

MINI SHRINK SYSTEM



DEMPACK Shrink System

DEMPACK TECHNICAL SPECIFICATIONS

The *DEMPACK Mini Shrink System* is a single step machine incorporating seal, trim and shrink into a single operation. The control panel interface is a touch panel with alphanumeric LCD display. This provides the operator with simple yet precise control of all machine operations, such as sealing temperature, shrink time and temperature for use with a wide variety of films including delicate films. Machine status and trouble shooting capability are available from the display. Several pre-programmed modes are available including seal only, seal and shrink and seal, cool and shrink.

The design provides for single maintenance and quiet operation. The seal elements are teflon coated and continuously cooled for maximum duty cycle and quality trim seals. The work table height is easily adjusted by placing the grid on the desired notches. The film separator and film cradle are mobile and individually adjustable for accurate positioning to match package size. The lid is held down in the operating position by an electromagnet freeing the operator for other functions and automatically released at cycle end. No special tool or custom installation is required.

Standard Features & Benefits of the *DEMPACK*

- Easy to program, for multiple products and delicate films on a single machine minimizing set up time.
- Closed circuit -water cooled jaws for maximum duty cycle.
- Easy to adjust work surface for fast physical change over from job to job.
- L-Sealer and Heat Tunnel combined into a single unit to reduce package handling time for increased throughput.
- Standard Film Perforation Wheel relieves pressure and "pillowing" effect from heat shrinking process.
- No tools needed for fast and easy setup.
- Magnetic hold down during complete machine cycle.

Technical Information

DEMPACK

Model	H 18	H 22
Electrical	220VAC 50/60Hz	
Power	2,300	3,600
Seal Bar Size	17" X 12" (440 X 300mm)	22" X 17" (600 X 430mm)
Max. Product Height inch (cm)	8-¼" (210mm)	10-¼" (260mm)
Average Output / Hour	200-300	200-300
Unit Dimensions (inch) W x D x H	48 ½ X 27 X 52	60 X 31 X 56
Unit Dimensions (cm) W x D x H	(123 X 68 X 131)	(152 X 78 X 143)
Shipping Size (inch) W x D x H	44 X 27 X 27	59 X 34 X 31
Shipping Size (cm) W x D x H	(111 X 68 X 69)	(149 X 86 X 78)
Shipping Weight	190 lbs (88Kg)	340 lbs (153Kg)

Audion Automation reserves the right to change these specifications without previous notice.



1533 Crescent Dr.
Carrollton, TX 75006 U.S.A.
Tel: 972.389.0777 • Fax: 800.875.5528
E-Mail: sales@audionltd.com
Website: www.audionautomation.com